


断电制动器--RB Series



- ▶ 弹簧式断电制动器
- ▶ Spring-applied power-off brake
- ▶ 可选装手动释放手柄
- ▶ Manual release shank in optional
- ▶ 可提供高防护等级的产品
- ▶ Higher protection class in optional
- ▶ 可提供永磁式制动器(RB300E / RB500E)
- ▶ Permanent magnet brake available(RB300E / RB500E)
- ▶ 根据要求, 可提供特殊制动扭矩的产品
- ▶ Special braking torque available on request

为了保护您控制系统中的直流接触器免遭击穿, 我们建议使用续流二极管。

To protect the DC contacts in your system against arcing, we recommend use of a freewheeling diode.

数据--Data								
型号 Type	工作电压 Operation voltage	制动扭矩 Braking torque	功率输入 Power input	电流消耗 Supply current	通电/断电时间 Pull in/Drop out time	工作制 Duty	绝缘等级 Insulation class	防护等级 Protection class
RB50	24V DC	50Ncm	7W	0.3A	<150/70ms	50%	F	20
RB150	24V DC	150Ncm	11W	0.48A	<150/70ms	50%	E	20
RB200	24V DC	200Ncm	11W	0.46A	<100/70ms	50%	E	20
RB300	24V DC	300Ncm	11W	0.48A	<150/70ms	50%	E	20
RB300E	24V DC	300Ncm	10.5W	0.44A	<15/25ms	50%	E	20
RB500E	24V DC	500Ncm	12W	0.5A	<50/30ms	50%	E	20

尺寸为毫米-Dimensions in mm					
	RB50	RB150	RB200	RB300	
D	47	52	52	57	
L	37	33	54	37	